

# Wireless Receiver ModBus / 0-10V / ES 1061

#### **Description**

Wireless receiver is used with our Wireless Sensors.

The receiver is placed out of the ventilation unit, heat pump etc. where it works as an antenna. The received signals are communicated to the control unit via ModBus. If only 1 sensor is to be connected the signal can also be chosen to be communicated as a 0-10V output signal.

When the receiver communicates via ModBus it is possible to connect up to 16 wireless sensors per receiver.

Wireless receiver can also be used to emulate up to 5 wired ModBus sensors.



#### Warning




ESD-Sensitive when lid is removed. Be certain to be ESD-discharged, so product isn't harmed.

#### <u>Mounting</u>

Must be mounted on a level, stable non-moving nor vibrating surface in a non-condensating environment. Avoid direct sunlight and thermal stress.

#### Connection



#### 0-10V output terminals

Terminal No.	Description			
5	0-10V out. Temperature (0-50°C)			
6	GND (0V)			
7	0-10V out. Relative Humidity (0-100%)			
8	GND (0V)			
9	0-10V out. CO <sub>2</sub> (0-2000ppm)			
10	GND (0V)			
11	No function.			
12	For future use			

0-10V output can only be used for sensor 0 and not in connction with emulation mode

#### **Modbus terminals**

Terminal No.	Description
1	ModBus A (D+)
2	ModBus B (D-)
3	GND (0V)
4	15-24V DC (only if DC-plug is not used)

#### **Technical Specifications**

 Supply:
 15-24V DC

 Enclosure:
 IP 20

 Dimension (HxWxD):
 86x154x34 mm

Number of 0-10V Output:

Communication Protocol: ModBus
Communication Interface: MiWi 868MHz



### DIP settings for use with ModBus

Baud rate	Sw1		
9600	OFF		
19200	ON		

Mode	RTU
Data bits	8

Parity	Stop bit	SW6	SW5
Even	1	OFF	OFF
ODD	1	OFF	ON
NONE	2	ON	OFF
NONE	1	ON	ON

## DIP settings for normal mode and emulation mode with wired ModBus sensors

	Node-ID	SW2	SW3	SW4
Emulation Mode (Emulation of wired sensors)	102-106 (Note 1)	OFF	OFF	OFF
Normal Mode	102	ON	OFF	OFF
	103	OFF	ON	OFF
	104	ON	ON	OFF
	105	OFF	OFF	ON
	106	ON	OFF	ON
	4	OFF	ON	ON
	5	ON	ON	ON

Note 1: (Emulation mode)

ID104 = Sensor3

#### **ModBus Register**

For further description and description of ModBus registers please refer to the manual. The manual can be downloaded by scanning the QR-code in bottom left corner or on the product. It can also be downloaded from our web-page.

Date: 19/06-2024 Drawn by: BJ/DF

Document No.: 949-208826 Wireless Receiver ModBus/0-10V ES1061

Rev.: 1.1

Manufactured by: LS Control A/S, Industrivej 12, DK-4160 Herlufmagle



QR-code for download of manual.